

## LED M Serie RF RGBW - M8/M4-5A

Referencecode: 2266800



General	
Product Type	Constant Voltage Driver
Length (mm)	104
Width (mm)	58
Height (mm)	9
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	42
Wire Strip Length	5mm
Wire Type	2.5mm2
Electronics	
nput Domain	DC
nput Voltage	5 ~ 24V DC
Output Voltage	5 ~ 24 V DC
Output Current (mA) max/output	5000
Output Current Max. (A)	20
Output Power (W)	240W @ 12V,
	100W @ 5V,
Power Supply	480W @ 24V N/A
LED Outputs	4
Lighting	
Color Range	RGBW
Control	
	RF, PWM-CV
Output Signal Control	Manual
	Buttons Control Panel
Driver Configuration Remote Distance	40m
Zones	40m
Number of Channels	4
Functions	programmable
	PLORI GITHITIADIC
Protection	
Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes
Environmental	
Environmental Operating Temperature	-20 ~ +55 °C

## **(€ ©** IP20

## Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.

Ltech Europe Page: 1/1 | | www.ltech-led.eu